

UNITED SR SPORT RACING

Blended with high performance, field proven additive to enhance the friction-reduction properties, United SR Sport Racing 100% Fully Synthetic motor oil is formulated to cater for motoring enthusiasts who having invested considerable time and money to upgrade and/or improve their engines performance are searching for that “unique” motor oil.

United SR Sport Racing 100% Fully Synthetic motor oil recognizes the importance of a properly formulated lubricant that can withstand extreme temperature at high rpm with minimum shearing the viscosimetry of the oil.

This product is test proven by motoring enthusiasts in endurance races in Australia, race circuits in New Zealand, Malaysia, Taiwan, Macau and Indonesia.

APPLICATIONS / BENEFITS

- Super fluidity over wide ranges of temperature and operating conditions.
- Excellent high temperature, high shear capability.
- Superior high temperature protection.
- Additional friction modifier for added protection.

TYPICAL CHARACTERISTICS

TEST DESCRIPTION	METHOD	TYPICAL RESULTS
SAE Viscosity Grade	SAE J 300	10W60
Specific Gravity @ 15 °C	ASTM D 4052	0.869
Flash Point, °C	ASTM D 92	234
Pour Point , °C	ASTM D 97	-39
Kinematic Viscosity @40°C	ASTM D 445	159.2
@100°C	ASTM D 445	22.6
Viscosity Index	ASTM D 2270	170
TBN, (mgKOH/g)	ASTM D 2896	10
Color	ASTM D 1500	<3.5

MEETS THE REQUIREMENTS OF

- API SN / SM